

FEP-0800 Version: 1



8-Port Fast Ethernet PoE Switch, 8 PoE Outputs

FEP-0800 is a 8-port 10/100Mbps Fast Ethernet Switch with Power over Ethernet (PoE) capability. With 8 dip switches, each PoE port can be manually set for On-Off control. FEP-0800 supports up to 30W on each LAN port when the DIP switch is in the ON position. Using a LevelOne PoE repeater, it is possible to extend the connection a further 100 meters, or even daisy-chain several PoE repeaters together for greater distances. Dual 10/100Mbps ports can connect with other edge switches or NVR as uplink ports.



1. LED Indicators
2. PoE Dip Switch
3. 10/100Mbps RJ-45 PoE Ports

4. Power Port
5. Wall-Mountable

Key Features

- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- PoE on/off control per port by dip switches
- Simple Plug and Play installation

Specifications

System Specifications

Standards & Protocols:

- IEEE 802.3 10-BASE-T, Ethernet
- IEEE 802.3u 100-BASE-TX, Fast Ethernet
- IEEE 802.3x Full-duplex Flow Control

**Buffer Memory:**

64KB

Port:

8 x 10/100Base-TX RJ-45 PoE Ports

Button/Knob:

PoE Power On/Off Switch

Indicator:

Power, Active, 10/100M, PoE

Transmission Method:

Store-and-Forward

Power Input:

56VDC

Power Consumption:

< 65W (FEP-0800W65)

< 90W (FEP-0800)

< 120W (FEP-0800W120)

Backplane (Gbps):

1.6Gbps

MAC Address Table:

1K

Data Rate:

10/100Mbps

Features

PoE:

Power Budget: Max. 60W (FEP-0800W65)

Max. 85W (FEP-0800)

Max. 115W (FEP-0800W120)

Power Output: 52V DC, up to 30W per port

Protection: PoE over current & PoE circuit sorting protection,

Pin Assignment: 4/5(+), 7/8(-)

Performance

Packet Forwarding Rate:

100Mbps port - 148,000pps

10Mbps port - 14,880pps

Environment

Operating Temperature (°C):

Operating: 0°C ~ 45°C

Storage: - 40°C ~ 70°C

Operating Humidity (Non-condensing):

Storage: 10% ~ 90%

Operating: 10% ~ 90%

Installation:

Desktop

Physical Specifications

Dimensions (W x D x H mm):

165 x 99 x 41 mm

Weight (g):


700g

Approval and Compliance

EMI/EMS:

FCC, CE, RoHS

Diagram



Order Information

FEP-0800: 90W

FEP-0800W65: 65W

FEP-0800W120: 120W

Package Contents

FEP-0800

Power Adapter

Power Cord

User Manual

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.