

**REF: FTTBox2U**

Combo 2 in 1 wall box / 19" sliding panel for 6 x LGX/MTP



LX12ALCADMONO



CAMTP6ASCOS2

Wall box or 19" 2U sliding panel

Other LGX modules available

## Applications

The FTTBox2U is a wall box for 6 x LGX modules / MTP cassettes, suitable as a floor box in FTTx applications. It can also be used as a sliding panel 2U when mounted in a 19" cabinet.

## General characteristics

- Metal wall box for 6 x LGX adapter plates or MTP cassettes.
- 19" sliding panel on 2U.
- Side patchcords exit.
- Receives up to 144fo or 72fo with SC simplex.
- IP20, suitable for indoor applications only.

## Physical properties

- Steel 12/10mm
- Electro static powder coating dark grey RAL 7016
- Operating temperature: -40°C to + 50°C
- 2 x Ø 20mm cable entries.
- 2 x Ø 25mm cable entries.
- Locking system including a key for a limited access of the splicing area
- Dimensions:
  - Width 430 mm x depth 285 mm x height 85 mm
  - Width when the door is open: 452 mm
- Weight: 4,3 kg
- Conditioning: unit

## REF: FTTBox2U

Combo 2 in 1 wall box / 19" sliding panel for 6 x LGX/MTP

### Related products

Part numbers	MTP preloaded cassettes	Packaging
Part numbers structure for MTP cassettes	CA MTP <b>xxA yyyy www</b>	Unit
Replace <b>xx</b> by the number of adapters	06 (SCD, LCQ,) or 12 (SCS, LCD)	
Replace <b>yyyy</b> by the type of adapters	SCS, SCD, SCAS, SCAD, LCD, LCQ, LCAQ	
Replace <b>www</b> by the type of fiber	OM1, OM2, OM3, OM4, OS2	
Part numbers	Loaded LGX modules	Packaging
Part numbers structure for LGX modules	<b>LX xxA yyyy www</b>	Unit
Replace <b>xx</b> by the number of adapters	06 or 12	
Replace <b>yyyy</b> by the type of adapters	6 adapters : SCD, SCAD, LCQ, LCAD, 12 adapters : SCS, SCAS, LCD, LCAD	
Replace <b>www</b> by the type of adapters	MUL (Multimode) MONO (Singlemode)	
Part numbers	Other modules	Packaging
LX OB	LGX blank module	Unit
LX PFB	LGX brush module	
LXU 06 SCD LCQ	LGX module for 6 adapters SCD or LCQ	
LXU 12 SCS LCD	LGX module for 12 adapters SCS or LCD	
LXU 06 KJ 6A FS TL	LGX module for 6 RJ45 BC6AFSTL	

### Standards

Tested to comply with the requirements of:

- TIA/EIA 568 C.3,
- ISO/IEC 11801 Amd 1.0/ Amd 2.0,
- EN 50173, EN 297-1
- IEC 60304, IEC 61754
- ROHS, REACH, SvHC

### Ordering Information

Part numbers	Description	Packaging
FTTBox2U	Combo wall box / 19" fixed panel 2U for 6 LGX/MTP	Unit
References for loaded box	FTTB 2U <b>xx Z yyyy www</b>	
Replace <b>xx</b> by the number of adapters/pigtails	144 adapters maxi, 288 pigtailes maxi (LC)	Unit
Replace <b>Z</b> by A or P	A pour for the adapters	
	P for the pigtailes (also with the adapters)	
Replace <b>yyyy</b> by the type of adapters	STS, FCS, SCS, LCD, SCAS, LCAD STD, FCD, SCD, LCQ, SCAD, LCAQ	
Replace <b>www</b> by the color of the adapters	MUL (beige), MONO (blue or green for APC)	
Replace <b>www</b> by the performance of the pigtailes	OM1, OM2, OM3, OM4, OS2, 7A2 (=G 657A2)	