


## NAC3FPXTOP

Chassis PowerCon True 1 TOP 16/20 A



### + ADVANTAGES

- True Outdoor Protection (TOP) Connector
- Waterproof and robust for harsh and demanding environments
- Can be connected and disconnected under load and voltage
- Easy and reliable «Twist-lock» system



## DESCRIPTION / APPLICATIONS

- Sound system
- Lights
- Signage and LED screens

## STANDARD

**CONNECTOR :** Certified ENEC - IEC 60320

and certified UL498

**INFLAMMABILITY :** UL 94 V-0

## ELECTRICAL CHARACTERISTICS

**CONTACT RESISTANCE :** 3m $\Omega$

**DIELECTRIC STRENGTH :**

4kVdc / 2.8 kVac

**INSULATION RESISTANCE :**

>0.1 G $\Omega$  IEC 68-2-30

**NUMBER OF ELECTRONICAL CONTACTS :**

2 + PE

**RATED CURRENT PER CONTACT :**

16 A rms

**RATED VOLTAGE :**

250 V ac

## MECHANICAL / TECHNICAL PROPERTIES

**LIFETIME:** >5000

**WIRESIZE :** 2.5mm<sup>2</sup>

**WIRESIZE :** 12 AWG

**CONTACTS :** Copper

**SHELL :** Polyamide

**RANGE TEMPERATURE :**

-30°C à +80°C

## ORDER INFORMATION

PART NB	DESCRIPTION	PACKAGING
NAC3FPXTOP	CHASSIS POWERCON TRUE 1 TOP 16/20 A	Individually