



PRODUCT INFORMATION

Capacitance between contacts :	≤ 4 pF
Contact resistance :	≤ 3 m Ω
Dielectric strength :	1,5 kVdc
Insulation resistance :	> 2 G Ω (initial)
Rated current per contact :	16A
Rated voltage :	< 50 V
Cable O.D.:	3.50 - 8.00 mm
Insertion force :	≤ 20 N
Withdrawal force:	≤ 20 N
Lifetime:	> 1000
Wiresize:	2,50 mm ²
Wiresize:	14 AWG
Wiring:	Solder contacts
Locking device :	Latch lock
Boot :	Polyurethane
Contact plating :	2 μ m Au
Contact :	Brass (CuZn39Pb3) mâle
Insert :	Polyamide (PA 6.6 30 % GR)
Locking element :	Zinc diecast (ZnAl4Cu1) Ck 67
Shell :	Black chromium
Shell plating :	Nickel

Flammability:	UL 94 HB
Standard compliance:	IEC 61076-2-103
Protection class:	IP 40
Solderability:	Complies with IEC 68-2-20
Temperature range:	-30 °C to +80 °C

Part nb

		
NC3FMCB	3 pole unisex XLR cable connector – Male / Female Gold contact – Black metal shell	1 unit