



NC5FXTOP

Cable Connector TOP Female 5 PTS



+ ADVANTAGES

- True Outdoor Protection (TOP) connector
- Waterproof and robust for harsh and demanding environments
- Power connector with breaking capacity
- Easy and reliable locking system



DESCRIPTION / APPLICATIONS

- Sound system
- Lights
- Signage and LED screens

STANDARD

CONNECTOR : Certified ENEC - IEC 60320

and certified UL498

INFLAMMABILITY : UL 94 HB

PROTECTION CLASS : IP 65, UL50E

ELECTRICAL CHARACTERISTICS

CAPACITANCE ENTRE CONTACTS : ≤ 4 pF
CONTACT RESISTANCE : ≤ 3 m Ω
DIELECTRIC STRENGTH : 1.5 kVdc
INSULATION RESISTANCE : >10 G Ω
NUMBER OF ELECTRONICAL CONTACTS : 7.5 A
RATED VOLTAGE : 50 V

MECHANICAL / TECHNICAL PROPERTIES

CABLE O.D. : 5.0 - 8.0 mm
INSERTION FORCE : ≤ 20 N
WITHDRAWAL FORCE : ≤ 20 N
LIFETIME : > 1000
WIRESIZE : max. 1.5mm²
WIRESIZE : max. 16 AWG

CONTACTS : Brass
SHELL : Zinc diecast
SEALING JACKET : UV - resistant rubber
TEMPERATURE RANGE :
-30°C to +80°C

ORDER INFORMATION

PART NB	DESCRIPTION	PACKAGING
NC5FXTOP	CABLE CONNECTOR TOP FEMALE 5 PTS	Individually