

TXVV-HDMI2SDI-TRUE1

Video converter - HDMI to SDI

Professional equipment in mission-critical applications is all about reliability and confidence. So we started with a clean sheet, and built what may soon become your most trustworthy piece of equipment.

Introducing the world's first video converters truly designed for the road. Video converters nowadays are used everywhere on professional A/V events, presentations, live shows and tours and often have a critical role. Yet, they are often the weakest link in the signal chain. Low quality connectors, weak enclosure, external consumer-grade power supply, and overall barebones design that all contribute to a generally unreliable piece of equipment. We wanted to change that, so we designed the Video Converters.






DESIGNED & MANUFACTURED
IN CANADA



FEATURES

- ✓ **Integrated power supply** with locking PowerCON True 1 Connector. Never rely on a cluster of wall-warts again.
- ✓ **Built-in convenience AC** outlet to power nearby projector, TV, laptop, small video projector... Power bar to power both the converter and device not required anymore.
- ✓ **Magnetic stacking system** and non-skid rubber pad for table top application. Saves at least 10 gaffer tape rolls a year.
- ✓ **Multiple mounting options** : C-Clamp, wall-mount adapter, LCD mount adapter and belt adaptor.
- ✓ **Rugged, Tour-ready and aesthetic enclosure** : The sexiest widget in your tool box, that will keep looking good for years to come.
- ✓ **Plug-n-play operation** ; No dipswitches, buttons or menus to fumble with : It just works.
- ✓ Clear and ample status **LED indicators** for quick troubleshooting.
- ✓ **Easy on-the-field identification** with unique color and alphabetic coding system.
- ✓ **Locking HDMI port** prevents accidental disconnection.
- ✓ **HDMI input tested and compatible with Apple** computers and iPad
- ✓ **Built-in Ethernet channel** for projector control, LAN extension and more.
- ✓ Integrated SDI splitter : **Dual SDI outputs.**
- ✓ Proudly designed and assembled **in Canada.**



CONNECTIONS

Video Input	HDMI 1.2 type A with lock system
Video Output	2 X 3G/HD/SD SDI BNC

SUPPORTED SIGNALS

3G Format Support	1080p50, 1080p59.94, 1080i50.
HD Format Support	720p50, 720p59.94, 720p60, 1080i50, 1080PsF23.98, 1080p24, 1080PsF24, 1080p25, 1080PsF25, 1080p29.97, 1080PsF29.97, 1080p30, 1080PsF30
SDI Format Support	525/23.98 NTSC, 525/29.97 NTSC.625/25 PAL.
SDI Video Sampling	4:2:2 and 4:4:4
SDI Audio Sampling	Sample rate of 48 kHz and 24 bit.
SDI Color Space	YUV and RGB
SDI Color Space	Automatically detects incoming signal format

PHYSICAL SPECIFICATIONS

Height	530mm (1.97 in)
Depth	180 mm (7.08 in)
Width	107 mm (4.21 in)
Weight	1 kg (2.2 lbs)

ENVIRONNEMENTAL SPECIFICATIONS

Relative Humidity	0 % to 90 % non-condensing
--------------------------	----------------------------

POWER REQUIREMENTS

Power supply	Built-in power supply PowerCON True1 input PowerCON True1 output
Power consumption	25 W
Operational voltage range	90-250 V with True1connectors
Courtesy outlet	Max 10 A, same voltage as input

IN THE BOX

- Converter HDMI to SDI (True 1)
- HDMI male with locking system to DVI male (1m)

CERTIFICATION

This device complies with the following international standards	CAN/CSA-C22.2 NO. 60950-1-07 UL 60950-1 FCC Part 15 Class A EN 60950-1, EN 55022
--	---

ORDERING INFORMATION

TXVV-HDMI2SDI-TRUE1HDMI to SDI converter (True1)	TXVV-SDI2SDI-TRUE1Dual Channel SDI Repeater (True1)
TXVV-SDI2HDMI-TRUE1 SDI to HDMI converter (True1)	XVV-CC1Video Converter Carrying Case for 1 unit
TXVV-SDIDA-TRUE1SDI Distribution Amplifier (4 outputs, True1)	XVV-CC2Video Converter Carrying Case for 2 units
TXVV-SDI2AUDIO-TRUE1 SDI Audio DeEmbedder (True1)	XVV-CC3Video Converter Carrying Case for 3 units