



WRE-8011E Version: 1

AC1200 Dual Band Wireless Range Extender, EU Power Plug

The LevelOne WRE-8011E is a versatile, easily deployed 802.11ac/n dual band Wi-Fi range extender that offers excellent throughput speed of up to 1200Mbps across both 2.4 and 5Ghz bandwidths combined, as well as high security. Perfect for expanding WLAN at home or in the office, the unit is designed for mounting to a wall, making WRE-8011E a good option for extending the range of the WLAN in a convenient and low profile deployment.

Key Features

- Provides stable signals and extends coverage
- Share your wireless network up to 1200Mbps
- Compatible with IEEE 802.11a/b/g/n/ac wireless standards
- Dual band technology reduces interference, providing reliable connections
- Simple wireless connectivity and security with WPS push button
- Wireless security with WPA/WPA2 and 64/128-bit WEP encryption

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.11e Wi-Fi Multimedia (WMM)

IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11AC Wireless Networking

Port:

1x 10/100Mbps Base-TX

Button/Knob:

WPS Button

Reset Button

Indicator:

Power, Wifi signal, WPS, LAN,

Power Input:

110-220VAC

Operating Temperature (°C):

Storage: -20 – 70°C

Operating: 0 – 40°C



Operating Humidity (Non-condensing):

Storage: 20 ~ 95%

Operating: 20 ~ 90%

Wireless

Operating Mode:

Repeater Mode, Bridge, AP

Encryption:

WEP 64/128-bit Web share key encryption WPA,WPA2,802.1x

WPA, WPA2-PSK TKIP/AES encryption, WPA-PSK802.1x

Receive Sensitivity(dBm):

2.4GHz:

802.11n (20MHZ_MSC0): Range?-85? dBm

802.11n (40MHZ_MCS0): Range (-82) dBm

802.11g 6Mbps: Range (-85) dBm

802.11g 54Mbps: Range (-68) dBm

802.11b 1Mbps: Range (-83) dBm

802.11b 11Mbps: Range (-76) dBm

5 GHz:

802.11a 6Mbps: Range (-85) dBm

802.11a 54Mbps: Range (-65) dBm

802.11n (20MHZ_MCS0): Range (-82) dBm

802.11n (40MHZ_MCS0): Range (-79) dBm

802.11ac (20MHZ_MCS0): Range (-82) dBm

802.11ac (40MHZ_MCS0): Range (-79) dBm

802.11ac (80MHZ_MCS0): Range (-76) dBm

Wireless Channels:

Ch.1 ~ 11 USA

Ch.1 ~ 13 EU

Ch.36~48

Ch. 52~ 165

EIRP(dBm):

(Controllable for different country regulations)

802.11ac: up to 15dBm \pm 1dBm

802.11n: up to 17dBm \pm 1dBm

802.11g: up to 20dBm \pm 1dBm

802.11b: up to 20dBm \pm 1dBm

Antenna:

2.4GHz : 2 x 3dBi Internal Antenna

5GHz: 2 x 4dBi Internal Antenna

Frequency Band:

2.4 ~ 2.4835 GHz

5.15 ~ 5.25 GHz

5.25 ~ 5.825 GHz

Data Transfer Rate:

802.11ac : 866Mbps

802.11n: 300 Mbps

802.11g: 54 Mbps

802.11b: 11 Mbps

Features

General:

VPN: PPTP, IPSec, L2TP Passthrough

Management:

Web-Based GUI Configuration

QoS:

IEEE 802.11e Wi-Fi Multimedia (WMM)

Ease of Use:

Web-based GUI with Quick Installation Wizard

Web-based (HTTP) firmware upgrade

Performance

Number of Clients:

20

Physical Specifications

Dimensions (W x D x H mm):

105 x 62 x 78 mm

Weight (g):

0.11kg

Approval and Compliance

EMI/EMS:

CE

Diagram



Order Information

WRE-8011E

Package Contents

WRE-8011E

Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.