

GEU-0822 Version: 1



Concentrateur gigabit 8 ports

Product Overview

The LevelOne GEU-0822 Gigabit Ethernet Switch is designed for reliable high-performance networking. With its non-blocking switching fabric in full-duplex mode, this switch can deliver up to 2000Mbps per port, while the Store-and-Forward service brings low latency and error-free packet delivery. This highperformance Gigabit Ethernet switch is perfect for fulfilling the demands of online gaming and multimedia streaming. Moreover, this switch also supports IEEE 802.3az Energy Efficient Ethernet which helps reduce power consumption.

Power Saving Features

The GEU-0822 supports IEEE 802.3az Energy Efficient Ethernet to provide power-saving benefits without compromising performance. One way is to automatically detecting the length of connected cables and to adjust power usage by saving energy on shorter cable connections.

Compact and Stylish Design

The stylish, compact wall-mountable housing of GEU-0822 fits any working environment. It comes with 8 x 10/100/1000Mbps ports to meet SOHO and home network expansion needs.

Easy to Use

The GEU-0822 features plug-and-play for easy installation. No configuration is required. Autonegotiation on each port senses the link speed of a network device and adjusts for compatibility and optimal performance.



1. LED Indicators
2. 10/100/1000Mbps RJ-45 Port
3. External power socket

Caractéristiques Principales

- 8 ports Ethernet gigabit
- Vitesse filaire de transmission et de réception des données de 10/100/1000 Mbit/s
- Trames étendues de 9K pour un débit optimal de transfert des données
- Prise en charge de l'auto-apprentissage et de l'auto-veillessement des adresses MAC 8K
- Montage bureau ou mural

Caractéristiques

Caractéristiques système

Normes et protocoles:

IEEE802.3(10BASE-T)

IEEE802.3u(100BASE-T)

IEEE802.3ab(1000BASE-T)

IEEE802.3az Energy Efficient Ethernet

Mémoire:

8Kbit

Mémoire tampon:

1Mbit

Port:

Full Shielded

Bouton/molette:

NO

Indicateur:

Power

LINK/ACT

1000M

Méthode de transmission:

Store- forward

Entrée d'alimentation:

DC 9V, 1A

Panneau arrière (Gbit/s):

16Gbps

Tableau d'adresses MAC:

8K

Caractéristiques

Général:

8 x 10/100/1000Mbps

Performances

Taux de transfert des paquets:

1488000pps

Trame étendue (K):

9KB

Conditions environnementales

Economie d'énergie:

YES

Température de fonctionnement (°C):

0-40°C

Hygrométrie de fonctionnement:

10%~90%

Spécifications physiques


Dimensions (L x P x H mm):

137x75x25mm

Poids (g):

300g

Schéma De Câblage



Informations Relatives À La Commande

Contenu De L'emballage

GEU-0822

Adaptateur d'alimentation

Manuel d'utilisation

Version CD du manuel d'utilisation

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.