

P/N: 48 BM OP 24 IP65 PN


Fiber IP65 wall box up to 24 fibers



P/N: 48BMOP24IP65N (loaded)



Loaded & ready to splice



Loaded with compact PLC splitter

Applications

The 24Fo IP65 fiber wall box is suitable for outdoor connections such as video security networks. The box will protect the connections for LAN or CAN from dust or water ingress. It is delivered unloaded and ready to receive 12 SC simplex or LC duplex adapters. It interconnects tight buffered, loose tube, pre-terminated or steel tape armoured cable.

General Characteristics

- Wall box suitable for 12 x simplex ST, FC, or ST or duplex LC MM or SM adapters.
- Up to 20 splices if used with duplex LC adapters, and 1 port for a PLC splitter,
- Up to 12 simplex SC, simplex FC, duplex LC, multimode or singlemode adapters.
- Up to 24 direct connections with duplex LC adapters, when splice tray is not used
- Including quick release cable management rings for bending radius protection
- Suitable for both indoor or outdoor applications
- 2 x 20mm Ø cable input & 12 outputs for drop cables of Ø 5.2mm

Physical properties

- ABS compound, black RAL9005 for UV protection
- IP65 rated, against dust and water ingress
- Operating temperature : -40°C to + 65°C
- 2 x 20mm cable entries
- Supplied with 24 heat shrinks, some snake tube, cable ties and wall mounting accessories
- Includes 2 stickers on the splice tray with FOTAG and France Telecom color coding
- Locking system including a key
- Dimensions :
 - *Width 168 mm x depth 65 mm x height 210mm*
- Weight : 0,85 kg

P/N: 48 BM OP 24 IP65 PN

Fiber IP65 wall box up to 24 fibers

Related products

| Part numbers | Description | Packing |
|--------------|---------------------------------------|---------|
| 48 MMT SCD | Multimode duplex SC UPC beige adapter | Unit |
| 48 SMT SCD | Singlemode duplex SC UPC blue adapter | Unit |
| 48 MMT LCQ | Multimode Quad LC UPC beige adapter | Unit |
| 48 SMT LCQ | Singlemode Quad LC UPC blue adapter | Unit |



48SMTSCD



Standards

Tested to comply with the requirements of :

- TIA/EIA 568 C.3,
- ISO/IEC 11801 Amd 1.0 / Amd 2.0,
- EN 50173, EN 297-1
- IEC 60304, IEC 61754
- ROHS, REACH, SvHC

Ordering Information

| Part number for unloaded box | Description | Packaging |
|---|---|-----------|
| 48 BM OP 24 IP65 PN | Black IP65 wall box up to 24 fibers | Unit |
| Part numbers for loaded boxes | 48BMOP xx Z yyyy www | Packaging |
| Replace xx by the number of adapters/pigtails | 12 adapters, 24 pigtails max (LC) | Unit |
| Replace Z by A or P | A: number of Adapters P: number of Pigtails + adapters | |
| Replace yyyy by the type of adapters | STS, SCS, SCAS, LCD, LCAD, | |
| Replace www by the color of adapters, | MUL(Beige), MONO (blue-green) | |
| Or replace www by the performances of pigtails | OM1, OM2, OM3, OM4, OS2 | |