

## CORD6AULXMSH

Pactch cord RJ45 CAT6A U/UTP LSZH LINK+ Range

### + AVANTAGES

- Wide range of length for different application
- Connexion on 2 levels for improving the next
- Overmolded sleeves
- Excellent transmission thanks to a very low resistivity



Available in 4 legnth different (1m - 2m - 3m - 5m)

### STANDARDS

| SYSTEME | ISO 11801 Ed 3 Class Ea |
|---------|-------------------------|
|         | EIA TIA 568-C.2 CAT6A   |
|         | EN 50173 Class Ea       |

### FEATURES

|                        |                              |
|------------------------|------------------------------|
| Fire resistance        | IEC 60332-1                  |
| Operating temperature: | -20° C / +70° C              |
| Minimum bending radius | 8 x diamètre du câble        |
| Compliant              | Conforme à la directive RoHS |

## ORDER INFORMATION

| P/N                  | DESIGNATION                                   | LENGTH | CONDITIONING |
|----------------------|-----------------------------------------------|--------|--------------|
| <b>CORD6AUL01MSH</b> | Pactch Cord RJ45 CAT6A U/UTP LSZH LINK+ Range | 1 m    | Unit         |
| <b>CORD6AUL02MSH</b> | Pactch Cord RJ45 CAT6A U/UTP LSZH LINK+ Range | 2 m    | Unit         |
| <b>CORD6AUL03MSH</b> | Pactch Cord RJ45 CAT6A U/UTP LSZH LINK+ Range | 3 m    | Unit         |
| <b>CORD6AUL05MSH</b> | Pactch Cord RJ45 CAT6A U/UTP LSZH LINK+ Range | 5 m    | Unit         |