# TECHNICAL DATASHEET

Ed2 050820 RN

### **CORD6AULXMSH**

LINK+ Range LSZH U/UTP RJ45 CAT6A Patch cord

## **BENEFITS**

- Different lengths available for different applications
- Connection on 2 levels for improving the NEXT
- Overmolded sleeves
- Excellent transmission thanks to a low contact resistivity









Available in 4 different lengths (1m - 2m - 3m - 5m)

#### **STANDARDS**

| SYSTEM | ISO 11801 Ed 3 Class Ea |
|--------|-------------------------|
|        | EIA TIA 568-C.2 CAT6A   |
|        | EN 50173 Class Ea       |

#### **FEATURES**

| Fire resistance        | IEC 60332-1        |  |
|------------------------|--------------------|--|
| Operating temperature: | -20° C / +70° C    |  |
| Minimum bending radius | 8 x cable diameter |  |
| Compliance             | RoHS compliant     |  |

#### ORDERING INFORMATION -

| P/N           | DESCRIPTION                                  | LENGTH | CONDITIONING |
|---------------|----------------------------------------------|--------|--------------|
| CORD6AUL01MSH | LINK+ Range LSZH U/UTP CAT6A RJ45 Patch Cord | 1 m    | Unit         |
| CORD6AUL02MSH | LINK+ Range LSZH U/UTP CAT6A RJ45 Patch Cord | 2 m    | Unit         |
| CORD6AUL03MSH | LINK+ Range LSZH U/UTP CAT6A RJ45 Patch Cord | 3 m    | Unit         |
| CORD6AUL05MSH | LINK+ Range LSZH U/UTP CAT6A RJ45 Patch Cord | 5 m    | Unit         |