


Insulation :

- PVC
- Color coding : black / red

Sheath :

- Black PVC
- Ø 10.20 mm



Conductor :

- Multi-strand bare copper
- Section : 4.00 mm²
- AWG : 11

Applications

- Wiring of all types of sound systems.
- Connection of amplifiers and speakers.
- Wiring of fixed and mobile installations.
- Public address.

Electrical properties

- Max. voltage : **300 V**
- Test voltage (50 Hz – 1 min) : **> 2000 V**
- Conductor resistance at 20°C:
 - Section 4.00 mm² : **< 4.95 Ω/km**
- Insulation resistance at 20°C : **> 100 MΩ.km**

Characteristics



- Temperature range: **Static : - 20°C → + 70°C**
Dynamic : - 10°C → + 70°C



- Minimum bending radius : **Static : 5 x Ø**
Dynamic : 10 x Ø



- Conform to RoHS directive



- Conform to **EN 50575 : 2014 + A1 : 2016**
- Euroclasse : **Eca**

Part nb

 REF.	Number of conductors	Section	$\text{mm} \leftarrow \text{ext.}$	$\text{Kg/Km} \leftarrow \text{MI}$	
FHP2400	2	4.00 mm ²	10.20 mm	130 kg / km	1000 m