

GEP-0812 Version: 1



8-Port Gigabit PoE Switch, 802.3at/af PoE, 4 PoE Outputs

The LevelOne GEP-0812 series provides 4 x 10/100/1000Mbps and 4 x 10/100/1000Mbps PoE Plus ports. This switch is IEEE 802.3af/at compliant, and provides power and data over a single Ethernet cable to any PoE device, with total power budget of 61.6W / 90W / 120W, up to 30W per port. Ideal for desktops and it is also 19-inch rack-mountable, which provides convenient and flexible installation. The GEP-0812 series is designed for small businesses that prefer an affordable solution for PoE deploying infrastructure.



1. LED Indicators
2. 10/100/1000Mbps RJ-45 PoE Ports
3. Power Port

Key Features

- 4 Gigabit ports and 4 Gigabit PoE ports
- Auto-detection and protection of non-standard PoE devices
- Supports 8K MAC address auto-learning and auto-aging
- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- 9K jumbo frames to increase data transfer rates
- 11-inch metal housing with 19-inch rackmount kit included
-
- 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
 IEEE 802.3u 100-BASE-TX, Fast Ethernet
 IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
 IEEE 802.3x Full-duplex Flow Control
 IEEE 802.3af Power over Ethernet (PoE)
 IEEE 802.3at Power over Ethernet Plus (PoE+)

Buffer Memory:

128KB

Port:

4 x 10/100/1000Base-TX RJ-45 PoE 1~4 Ports

4 x 10/100/1000Base-TX RJ-45 Uplink 5~8 Ports

Indicator:

Power, Active, 10/100/1000M, PoE

Transmission Method:

Store-and-Forward

Power Input:

100-240V AC, 50-60 Hz, 2A Internal Power Supply

Power Consumption:

< 65W (GEP-0812)

< 90W (GEP-0812W90)

< 120W (GEP-0812W120)

Backplane (Gbps):

16Gbps

MAC Address Table:

8K

Data Rate:

10/100/1000Mbps

Features

PoE:

Power Budget: Max. 60W (GEP-0812)

Max. 85W (GEP-0812W90)

Max. 115W (GEP-0812W120)

PoE Standard: IEEE 802.3af/at Power over Ethernet / PSE

PD classification identity

PoE over current protection

PoE circuit sorting protection

PoE Power Output: Per Port 56V DC, Max. 15.4 watts (IEEE 802.3af) or 30 watts (IEEE 802.3at)

Power Pin Assignment: 1/2(+), 3/6(-)

Performance

Packet Forwarding Rate:

1000Mbps port - 1488,000pps

100Mbps port - 148,000pps

10Mbps port - 14,880pps

Jumbo Frame (K):

9K

Environment

Operating Temperature (°C):

Operating: 0°C ~ 45°C

Storage: - 40°C ~ 70°C

Operating Humidity (Non-condensing):

Storage: 10% ~ 90%

Operating: 10% ~ 90%

Installation:
Desktop and 19-inch rack-mountable

Physical Specifications


Dimensions (W x D x H mm):
280 x 125.5 x 44mm

Weight (g):
1500g

Approval and Compliance

EMI/EMS:
FCC, CE, RoHS

Diagram



Order Information

GEP-0812: 65W
GEP-0812W90: 90W
GEP-0812W120: 120W

Package Contents

GEP-0812
Power Cord
19" Rack Mount Kit
Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.